



wirefield

PROLED 100 ALED

100,000 hrs
L80/B50


SURFACE
MOUNTED



Technical Specification

- Polycarbonate body and diffuser.
- Surface mount.
- Captive clips to assist with installation.
- IP65.
- IK06.
- Integral emergency available.

Features


Wattage	15w to 23w
Lumens per Watt	Up to 102
CRI	80
L**B**	100,000 hours L80 B50
Driver	Fixed Output / Dali / 1-10V / Corridor Function
Controls	Microwave / 
Colour Temperature	4000k
Temperature Rating	-20°C to +30°C (excluding emergency)

LIGHTING INNOVATION FOR AMENITY APPLICATIONS

wirefield PROLED 100 ALED

Product Specification

Code	Watts	Delivered lumens	D (mm)	Ø (mm)
ALED15	12	1660	120	385
ALED23	23	3255	120	385



Control Options

Driver Options:

Fixed Output

DALI Driver

1-10v

Corridor Function

Sensor Options:

Microwave

Eye-Wi

LED Options

Additional Options:

CCT 3000K / 6000K

Emergency Options

Emergency Options:

3hr Integral Maintained

3hr Integral Maintained Self Test

3hr Integral Maintained Self Test with Eye-Wi Reporting

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

LIGHTING INNOVATION FOR AMENITY APPLICATIONS

Tel: 0844 847 5100 Fax: 0844 847 5101 Web: www.wirefield.co.uk Email: sales@wirefield.co.uk

WIREFIELD 201901 V1.0