



wirefield

PROLED 100 HSS LG3

100,000 hrs
L80/B50

SUSPENDED
LINEAR



Technical Specification

- Steel body with double parabolic aluminium louvred LED modules.
- Suspended - 70% down - 30% up, light distribution.
- Available with connection accessory for continuous run.
- IP40.
- IK05.
- Integral emergency available.
- UGR <19.
- RAL colour options.
- LG3 compliant.

Features

Wattage	31w to 57w
Lumens per Watt	Up to 132
CRI	80
L**B**	100,000 hours L80 B50
Driver	Fixed Output / Dali / Switch Dim
Controls	Microwave Sensor / Bluetooth / Integral Daylight Sensor / CF / Smart Sensor
Colour Temperature	4000k
Temperature Rating	0°C to +35°C (excluding emergency)

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS

Product Specification

Code	Watts	Total Delivered lumens*	L x W x D (mm)	Weight (kg)
HSS1314KALG3	31	4084	1215 x 175 x 40	4.1
HSS1474KBLG3	47	6263	1555 x 175 x 40	5.5
HSS1574KBLG3	57	7330	1555 x 175 x 40	5.5

* 70% DOWN - 30% UP, LIGHT DISTRIBUTION



Control Options

Driver Options:

Fixed Output

DALI

Switch Dim

Sensor Options:

Microwave Sensor

Bluetooth Control

Integral Daylight Sensor

Corridor Function

Smart Sensor

LED Options

Additional Options:

CCT 3000K

Emergency Options

Emergency Options:

3hr Integral Maintained

3hr Integral Maintained Self Test

3hr Integral Maintained with DALI Interface

Integral Emergency with 'Escape Route' Optic

Integral Emergency with 'Open Area' Optic

Accessories

Optional Accessories:

RAL Colour Options

Joint Pieces for Continuous Run

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS