



wirefield PROLED 100 OCR

100,000 hrs
L80/B50


**RECESSED
MODULAR**



Technical Specification

- Steel body with perimeter opal diffuser.
- Recessed mounted into a 15mm/24mm ceiling grid.
- Low impact design
- IP40.
- IK05.
- Integral emergency available.
- RAL colour options.


Features

Wattage	29w to 57w
Lumens per Watt	Up to 107
CRI	80
L**B**	100,000 hours L80 B50
Driver	Fixed Output / Dali / 1-10V
Controls	PIR / Microwave / 
Colour Temperature	4000k
Temperature Rating	0°C to +35°C (excluding emergency)

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS

Product Specification

Code	Watts	Delivered lumens	L x W x D (mm)	Weight (kg)
OCR1294KB	29	3006	595 x 595 x 70	4.5
OCR1394KB	39	4227	595 x 595 x 70	4.5
OCR1574KB	57	5859	595 x 595 x 70	4.5



Control Options

Driver Options:

Fixed Output

DALI Driver

1-10v

Corridor Function

Sensor Options:

PIR

Microwave

Eye-Wi

LED Options

Additional Options:

CCT 3000K

Emergency Options

Emergency Options:

3hr Integral Maintained

3hr Integral Maintained Self Test

3hr Integral Maintained Self Test with Eye-Wi Reporting

Accessories

Optional Accessories:

IP44 Housing

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS